碟管式反渗透膜/DTRO							
产品参数 / Membrane Specifications							
膜组件型号/(Membrane product model)	DTGE	DTGE-MP	DTGE-HP	DTGE-HHP			
压力等级	75	90	120	180			
膜面积m²/ (Membrane area)	9.45						
膜片数量/	209						
操作温度(℃)	40						
长度 (mm)	1400						
直径 (mm)	214	218	224	234			
重量 (mm)	67	82	88	120			
产品外形图/Product outline drawing							



型号/尺寸	D_{o} (mm)	L_1 (mm)	L_2 (mm)	L_{3} (mm)
DTGE	220	1410	1200	1100
DTGE-MP	220	1410	1200	1100
DTGE-HP	220	1410	1200	1100
DTGE-HHP	220	1410	1200	1100

温馨提示/Tips

1.在任何情况下,超滤膜组件都不允许出现冰冻现象,如在特殊地区或有特殊要求,应添加防冻液以确保运输安全,有关防冻液知识请参考产品手册。

Under any condition, should the ultrafiltration membrane module be allowed to freeze. If it is in a special area or has special requirements, should be added to ensure safe transportation. Please refer to the product manual for antifreeze knowledge.

2.超滤膜组件必须在产品手册所规定的运行条件下使用,在未得到阿克菲姆公司书面形式承诺或通知情况下,任何不符合手册要求的设计和使用都将视作对质量 保证的放弃。Ultrafiltration membrane modules must be used under the operating conditions specified in the product manual. Any design and use that does not meet the requirements of the manual will be considered a waiver of quality assurance without written commitment or notification from agfilm.